

A&D Weighing GF-G Series

Toploader Balances



STANDARD FEATURES

- Super hybrid sensor technology
- One second response time
- Data memory function
- RS-232C standard
- Clear VFD display
- GLP/LIMS/ISO compliance
- Standard WinCT software
- Five-year warranty
- Underhook
- External calibration only (Canadian approval number AM-5587)
Grams only (no multiple units of measure)

OPERATING TEMPERATURE:

41°F to 104°F (5°C to 40°C)

LINEARITY:

GF-200G, GF-300G: +/-0.002 g
GF-1200G, GF-2000G, GF-3000G: +/-0.02 g
GF-6000G: +/-0.1 g

REPEATABILITY/STANDARD DEV.:

GF-200G, GF-300G, GF-1200G: +/- 0.001 g
GF-2000G, GF-3000G: +/-0.01 g
GF-6000G: +/-0.1 g

STABILIZATION TIME:

GF-200G, GF-300G, GF-1200G, GF-2000G,
GF-3000G, GF-6000G: Approx. 1 second
(typical in fast mode)

WEIGHT:

GF-200G, GF-300G: 10.12lb/4.6kg
GF-1200G, GF-2000G, GF-3000G,
GF-6000G: 11.2lb/5.1kg

WEIGHING MODES:

Animal weighing, comparator function,
ACAI counting function, percentage function,
density determination

WARRANTY:

Five-year limited warranty

GF-G SERIES CAPACITIES

	GF-200G	GF-300G	GF-12	GF-3000G	GF-6000G
g	210 x 0.001	310 x 0.001	410 x 0.001	610 x 0.001	810 x 0.001

A&D Weighing GF-P Series

Toploader Balances



STANDARD FEATURES

- Pill counting feature also complies with Handbook 44 requirements
- Fast, Super Hybrid Sensor (SHS) gives you the ultimate in response speed-just one second
- Nine weighing modes
- GLP/GMP/ISO compliance
- WinCT data collection software included free
- Tough die-cast aluminum housing
- Removable stainless steel pan (5in x 5in)
- NTEP and Pharmacopia approved (CofC# 04-077P)
- IP54 splash proof operator keyboard protects against dust and spills, stainless steel weigh pan
- Data memory function
- Vacuum fluorescent display

SPECIFICATIONS

CAPACITY (g):

GF-200P: 210g x 0.001 g
GF-300P: 310g x 0.001 g

OPERATING TEMPERATURE:

41°F to 104°F (5°C to 40°C)

LINEARITY:

GF-200P, GF-300P: ±0.002 g

REPEATABILITY/STANDARD DEV.:

GF-200P, GF-300P: 0.001 g

STABILIZATION TIME:

GF-200P, GF-300P: Approx. 1 second
(typical in fast mode)

WEIGHT:

GF-200P, GF-300P: 10.12lb/4.6kg

WEIGHING MODES:

Animal weighing, comparator function,
ACAI counting function, percentage function,
density determination

PAN SIZE:

5in x 5in

WARRANTY:

Five-year limited warranty

GF-G Series

PART #	A&D MODEL #	CAPACITY	EST. SHIP WEIGHT
102892.....	GF-200G	210g x 0.001 g with breeze break (3.6in high).....	11.2lb/5.1 kg.....
102893.....	GF-300G	310g x 0.001 g with breeze break (3.6in high).....	11.2lb/5.1 kg.....
102894.....	GF-1200G	1210g x 0.01 g	11.2lb/5.1 kg.....
102895.....	GF-2000G	2100g x 0.01 g	11.2lb/5.1 kg.....
102896.....	GF-3000G	3100g x 0.01 g	11.2lb/5.1 kg.....
102897.....	GF-6000G	6100g x 0.1 g	11.2lb/5.1 kg.....

OPTIONS/ACCESSORIES

97695.....	GX-04.....	Comparator output	
97696.....	GX-06.....	Analog output; factory installed only	
97697.....	GX-10.....	Glass breeze break for GF-200G/300G.....	
97698.....	GX-11.....	Glass breeze break for GF-1200G/2000G/3000G/600G	
97699.....	GX-12.....	Animal weighing pan for GF-1200G/2000G/3000G/6000G.....	
97700.....	GX-13.....	Density determination kit for GF-200G/300G.....	
97701.....	GX-29.....	Bluetooth®, factory installed, 30ft maximum.....	
97702.....	CC:102E.....	Storage/Carrying case	
97607.....	AD-1682.....	Rechargeable battery pack	
97608.....	AD-8920.....	Universal remote display.....	
97605.....	AD-100-2	Anti-theft device	
97612.....	SW:128	Foot switch	
97703.....	AX:073003691-S... ..	Protective in-use cover for GF-200G/300G	
97704.....	AX:073003692-S... ..	Protective in-use cover for GF-1200G/2000G/3000G/6000G	
97649.....	TB:110C.....	AC adapter (120V)	
97631.....	TB:123	AC adapter (220V)	
102891.....	GX-02.....	USB option	

Bluetooth is a registered trademark of Bluetooth SIG

GF-P Series

PART #	A&D MODEL #	CAPACITY	EST. SHIP WEIGHT
97799.....	GF-200P.....	210g x 0.001 g with standard breeze break	11 lb/5.2 kg
97800.....	GF-300P.....	310g x 0.001 g with standard breeze break	11 lb/5.2 kg

OPTIONS/ACCESSORIES

97697.....	GX-10.....	Glass breeze break for GF-200 & 300	
97703.....	AX:073003691-S... ..	Protective in-use cover for GF-200/300 (each)	
97649.....	TB:110C.....	AC adapter (120V)-standard with unit	
97801.....	TB:110CL.....	90° angle AC adapter (120V).....	
97631.....	TB:123	AC adapter (220V)	
102891.....	GX-02.....	USB option	

C&M SCALE
 CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
 Phone # (708) 771-0100
 Fax # (708) 771-0195