



STANDARD FEATURES

- Internal calibration weight
- Auto environmental compensation
- IP54 splash proof operator keyboard
- Standard RS-232C bidirectional communication for Windows® compatible data collection software
- GLP/GMP/ISO compliant to either AD-8121 printer or computer. Transmits date, time, ID number, serial number and calibration data
- Auto re-zero function
- Interval time setting
- Rechargeable battery option for portable needs
- Data memory function
- Multiple weighing modes
- Quick reference operation card
- Time and date built-in
- Vacuum florescent display
- Optional glass breeze break
- Underhook weighing

SPECIFICATIONS

OVERALL DIMENSIONS: (W x D x H)

8.26in x 12.48in x 3.38in
210mm x 317mm x 86mm

DISPLAY REFRESH:

Five times per second (stable)/10 times per second (unstable)

OPERATING TEMPERATURE:

41°F to 104°F (5°C to 40°C) RH<85%

PERCENTAGE MIN. DIV.:

0.01%

POWER:

110, 120, 210, 220VAC, 50/60Hz

LINEARITY:

GX-200, GX-400: ±0.002g
GX-600, GX-800, GX-1000: ±0.003g
GX-2000, GX-4000: ±0.02g
GX-6100: ±0.03g
GX-6000, GX-8000: ±0.1g

REPEATABILITY/STANDARD DEV.:

GX-200, GX-400, GX-600, GX-800,
GX-1000: 0.001g
GX-2000, GX-4000, GX-6100: 0.01g
GX-6000, GX-8000: 0.1g

STABILIZATION TIME:

GX-200, GX-400, GX-600, GX-2000,
GX-4000, GX-6000, GX-8000:
Approx. 1 second (typical in fast mode)
GX-800, GX-1000, GX-6100:
Approx. 1.5 seconds

WEIGHT:

GX-200, GX-400, GX-600, GX-800,
GX-1000: 4.6kg/10.1lb
GX-2000, GX-4000, GX-6100,
GX-6000, GX-8000: 5.1kg/11.2lb

WEIGHING MODES:

Animal weighing, comparator function,
ACAI counting function, percentage function,
density determination

WARRANTY:

Five-year limited warranty

GX SERIES CAPACITIES

	GX-200	GX-400	GX-600	GX-800	GX-1000	GX-2000	GX-4000
g	210 x 0.001	410 x 0.001	610 x 0.001	810 x 0.001	1100 x 0.001	2100 x 0.01	4100 x 0.01
oz	7.40755 x 0.00005	14.46230 x 0.00005	21.51710 x 0.00005	28.57190 x 0.00005	38.80135 x 0.00005	74.0755 x 0.0005	144.6230 x 0.0005
lb	0.462970 x 0.000005	0.903895 x 0.000005	1.344820 x 0.000005	1.785744 x 0.000005	2.425084 x 0.000005	4.62970 x 0.00005	9.03895 x 0.00005
ozt	6.75165 x 0.00005	13.18180 x 0.00005	19.61195 x 0.00005	26.04210 x 0.00005	35.36582 x 0.00005	67.5165 x 0.0005	131.8180 x 0.0005
dwt	135.033 x 0.001	263.636 x 0.001	392.239 x 0.001	520.842 x 0.001	707.316 x 0.001	1350.33 x 0.01	2636.36 x 0.01
ct	1050.000 x 0.005	2050.000 x 0.005	3050.000 x 0.005	4050.000 x 0.005	5500.000 x 0.005	10500.00 x 0.05	20500.00 x 0.05
mm	56.0000 x 0.0005	109.3335 x 0.0005	162.6665 x 0.0005	215 x 0.0005	270 x 0.0005	560.000 x 0.005	1093.335 x 0.005
gn	3240.80 x 0.02	6327.26 x 0.02	9413.74 x 0.02	12500.21 x 0.02	16975.6 x 0.02	32408.0 x 0.2	63272.6 x 0.2

	GX-6100	GX-6000	GX-8000
g	6100 x 0.01	6100 x 0.1	8100 x 0.1
oz	215.1710 x 0.0005	215.170 x 0.005	285.720 x 0.005
lb	13.44820 x 0.00005	13.4480 x 0.0005	17.8575 x 0.0005
ozt	196.1195 x 0.0005	196.120 x 0.005	260.420 x 0.0005
dwt	3922.39 x 0.01	3922.4 x 0.1	5208.4 x 0.1
ct	30500.00 x 0.05	30500.0 x 0.5	40500.0 x 0.5
mm	1626.665 x 0.005	1626.65 x 0.05	2160.00 x 0.05
gn	94137.4 x 0.2	94136 x 2	125002 x 2

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195

PART #	A&D MODEL #	CAPACITY	EST. SHIP WEIGHT
97685.....	GX-200.....	210g x 0.001 g with standard breeze break.....	10.11 lb/4.6 kg.....
97686.....	GX-400.....	410g x 0.001 g with standard breeze break.....	10.11 lb/4.6 kg.....
97687.....	GX-600.....	610g x 0.001 g with standard breeze break.....	10.11 lb/4.6 kg.....
97688.....	GX-800.....	810g x .001 g with standard breeze break.....	10.11 lb/4.6 kg.....
97689.....	GX-1000.....	1100g x .001 g with standard breeze break.....	10.11 lb/4.6 kg.....
97690.....	GX-2000.....	2100g x 0.01 g.....	11.2 lb/5.1 kg.....
97691.....	GX-4000.....	4100g x 0.01 g.....	11.2 lb/5.1 kg.....
97692.....	GX-6100.....	6100g x 0.01 g.....	11.2 lb/5.1 kg.....
97693.....	GX-6000.....	6100g x 0.1 g.....	11.2 lb/5.1 kg.....
97694.....	GX-8000.....	8100g x 0.1 g.....	11.2 lb/5.1 kg.....

OPTIONS/ACCESSORIES

97695.....	GX-04.....	Comparator output; factory installed only.....	
97696.....	GX-06.....	Analog output; factory installed only.....	
97697.....	GX-10.....	Glass breeze break for GX-200/400/600.....	
97698.....	GX-11.....	Glass breeze break for GX-2000/4000/6100/6000/8000.....	
97699.....	GX-12.....	Animal weighing pan for GX-400/600/2000/4000/6100/6000/8000.....	
97700.....	GX-13.....	Density determination kit for GX-200/400/600.....	
97701.....	GX-29.....	Bluetooth®, factory installed, 30ft maximum.....	
97702.....	CC:102E.....	Storage/Carrying case.....	
97607.....	AD-1682.....	Rechargeable battery pack.....	
97608.....	AD-8920.....	Universal remote display.....	
97605.....	AD-100-2.....	Anti-theft device.....	
97612.....	SW:128.....	Foot switch.....	
97703.....	AX:073003691-S.....	Protective in-use cover for GX-200/400/600.....	
97704.....	AX:073003692-S.....	Protective in-use cover for GX-2000/4000/6100/6000/8000.....	
97649.....	TB:110C.....	AC adapter (120V).....	
97631.....	TB:123.....	AC adapter (220V).....	
102891.....	GX-02.....	USB option.....	

Bluetooth is a registered trademark of Bluetooth SIG

C&M SCALE
 CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
 Phone # (708) 771-0100
 Fax # (708) 771-0195