



STANDARD FEATURES

- Internal calibration
- Auto environmental compensation
- IP-65/NEMA4
- Standard RS-232C bidirectional interface
- GLP/GMP/ISO compliant to either AD-8121B printer or computer. Transmits date, time, ID number, serial number and calibration data
- Data memory function
- Multiple weighing modes
- Quick reference operation card
- Time and date
- Vacuum fluorescent display

SPECIFICATIONS

CAPACITY (g):

- GX-8K: 8.1 kg x 0.01 g
- GX-8K2: 8.1 kg/2.1 kg x 0.1 g/0.01 g
- GX-10K: 10.1 kg x 0.01 g
- GX-12K: 12 kg x 0.1 g
- GX-20K: 21 kg x 0.1 g
- GX-30K: 31 kg x 0.1 g
- GX-32K: 31 kg/6.1 kg x 1 g/0.1 g

UNITS OF MEASURE:

- oz, lb, lb-oz, ozt, dwt, ct, mm GN, pcs, %, custom

LINEARITY:

- GX-8K: ±0.02 g
- GX-8K2: ±0.1 g, ±0.02 g
- GX-10K: ±0.03 g
- GX-12K, GX-20K, GX-30K: ±0.2 g
- GX-32K: ±1 g/±0.2 g

REPEAT./STD.DIV.:

- GX-8K: 0.01 g
- GX-8K2: 0.05 g/0.01 g
- GX-10K: 0.01 g
- GX-12K, GX-20K, GX-30K: 0.1 g
- GX-32K: 0.5 g/0.1 g

PAN SIZE: (W X D)

- 10.62 in x 8.26 in
- 270 mm x 210 mm

DIMENSIONS (W x D x H):

- 11.81 in x 13.98 in x 4.37 in
- 300 mm x 355 mm x 111 mm

WEIGHT:

- 18.3lb/8.3kg

SENSITIVITY DRIFT (-10 TO +30°C):

- GX-8K, GX-10K: ±2 ppm/°C
- GX-8K2, GX-12K, GX-20K, GX-30K: ±3 ppm/°C
- GX-32K: ±5 ppm/°C

OPERATING TEMPERATURE:

- 41°F-104°F/-5°C-40°C

DISPLAY REFRESH:

- Five times per second (stable)/10 times per second

STABILIZATION TIME:

- Approx. 1.5 seconds (typical in fast mode)

WARRANTY:

- Five-year limited warranty

PART #	A&D MODEL #	CAPACITY	CALIBRATION MASS	EST. SHIP WEIGHT
97775.....	GX-8K2.....	2/8kg x 0.01/0.1 g.....	2-8kg.....	18.3lb/8.3kg.....
97776.....	GX-8K.....	8kg x 0.01 g.....	8kg.....	18.3lb/8.3kg.....
97777.....	GX-10K.....	10.1 kg x 0.01 g.....	10kg.....	18.3lb/8.3kg.....
97778.....	GX-12K.....	12 kg x 0.1 g.....	10kg.....	18.3lb/8.3kg.....
97779.....	GX-20K.....	20kg x 0.1 g.....	20kg.....	18.3lb/8.3kg.....
97780.....	GX-30K.....	30kg x 0.1 g.....	30kg.....	18.3lb/8.3kg.....
97781.....	GX-32K.....	6/30kg x 0.1/1 g.....	30kg.....	18.3lb/8.3kg.....

OPTIONS/ACCESSORIES

97782.....	GX-04K*.....	Comparator/output and RS-232C/20mA interface.....
97783.....	GX-06K*.....	Analog output/20mA interface.....
97784.....	GX-07K**.....	Waterproof cable for standard RS-232C.....
97701.....	GX-29.....	Bluetooth®, factory installed, 30 ft maximum.....
97605.....	AD-100-2.....	Anti-theft device.....
97785.....	AX-073007197A.....	Protective in-use cover.....
97649.....	TB:110C.....	AC adapter (120 V).....
97631.....	TB:123.....	AC adapter (240 V).....
102898.....	GXK-31.....	Draft shield.....
102899.....	GXK-12.....	Annual weighing pan.....

*GX-04K, GX-06K, replace standard RS-232C and cannot be used at the same time. IP-65 rating does not apply when the GX-04K or the GX-06K is installed.

**Use the GX-07K optional waterproof RS-232C cable, in order to use the standard RS-232 interface for water and dust proof (IP65)

Bluetooth is a registered trademark of Bluetooth SIG