

Ohaus® CS Compact Series

Portable Electronic Scales



APPROVALS



STANDARD FEATURES

- Superior RF protection
- Reliable, stable results
- Approvals include CE listed and FCC Class B Part 15 operation
- Large removable stainless steel weighing platform
- Low profile design
- Standard AC adapter
- Easy operation
- Low battery indicator
- Auto shut-off feature
- Overload protection
- Push-button calibration

SPECIFICATIONS

CAPACITY:

CS200: 200g
CS2000, CS2000P: 2000g
CS5000, CS5000P: 5000g

READABILITY:

CS200, CS200P: 0.1g;
CS2000, CS2000P: 1g;
CS5000, CS5000P: 2g;

OVERALL DIMENSIONS:

8.0 x 5.5 x 1.5in
(20.3 x 14.0 x 3.8cm)

DISPLAY:

LCD 0.43 (11mm)

ZERO RANGE:

Full capacity by subtraction

OPERATING TEMPERATURE: (OPTIMUM)

65°F to 77°F (18°C to 25°C) at 10%
to 80% relative humidity, non-condensing

POWER:

Three AA alkaline batteries (included) or AC
adapter (included)

REPEATABILITY (STD. DEV):

CS200: 0.1g
CS2000, CS2000P: 1g
CS5000, CS5000P: 2g

LINEARITY:

CS200: ±0.1g
CS2000, CS2000P: ±1g
CS5000, CS5000P: ±2g

CALIBRATION:

User calibration for keypad

STABILIZATION TIME:

3 seconds

PAN SIZE:

5.75in diameter (146.05mm dia)

AUTO SHUT-OFF:

5 minutes no activity
(battery operation only)

WEIGHING UNITS:

g, lb:oz, Newton

WARRANTY:

One-year limited warranty

Ohaus® CL Compact Series



STANDARD FEATURES

- Basic weighing with simple 2-button keypad
- Superior RF protection
- Large weighing platform
- Stackable design with integrated shipping lock
- Low battery indicator
- Auto shut-off feature
- Mechanical and software overload protection
- External push-button calibration
- Battery (standard) or AC adapter (optional) operation

SPECIFICATIONS

CAPACITY:

CL201: 200g
CL2000: 2000g
CL5000: 5000g

READABILITY:

CL201: 0.1g
CL2000; CL5000: 1g

OVERALL DIMENSIONS:

5.5 x 1.6 x 7.9in
(14 x 4.0 x 20cm)

ZERO RANGE:

To capacity by subtraction

OPERATING TEMPERATURE: (OPTIMUM)

65°-77°F (18°-25°C)

POWER:

3 AA batteries (included)
AC adapter (optional)

LINEARITY:

CL201: +/- 0.1g
CL2000; CL5000: +/- 1g

CALIBRATION:

Digital calibration from keypad

STABILIZATION TIME:

3 seconds

WEIGHING UNITS:

g, lb:oz, ozt, dwt

PAN SIZE:

4.75in/12.0cm (diameter)

DISPLAY:

LCD (0.5in/1.2cm)

NET WEIGHT:

0.875lb/0.4kg

AUTO SHUT-OFF:

5 minutes no activity (battery operation only)

WARRANTY:

One year limited warranty

CS Compact Series

PART #	OHAUS MODEL #	DESCRIPTION	EST. SHIP WEIGHT
53493.....	CS200	200g x 0.1 g, 0lb; 7.05oz x 0.01 oz.....	2 lb
53494.....	CS2000	2,000g x 1 g, 4lb; 6.55 oz x 0.05oz.....	2lb
53495.....	CS5000	5,000g x 2g, 11lb; 0.4oz x 0.1 oz.....	2lb
53496.....	CS2000P*	Postal 2000g x 1 g, 4lb; 6.55 oz x 0.05 oz	2lb
53497.....	CS5000P*	Postal 5000g x 2g, 11lb; 0.4 oz x 0.1 oz	2lb
83225.....	CS200P	Postal, 200g x 0.1 g/0lb, 7 oz x 0.01 oz.....	2 lb
91710.....	CS2000PS	Postal, 2,000g x 1 g with gs letter holder.....	2lb

* U.S. Postal chart included

OPTIONS/ACCESSORIES

33423.....	90524-66	AC adapter (for CSXXXXX models)	
70430.....	80500457	AC adapter (for CS-XXXXX models)	
70434.....	80850075.....	Bowl, 1050mL	
70435.....	80850076.....	Stainless steel weighing pan cover	
70436.....	80850097	Additional U.S. postal chart	

CL Compact Series

PART #	OHAUS MODEL #	DESCRIPTION	EST. SHIP WEIGHT
103101.....	CL201	200g x 0.1 g	2 lb
103102.....	CL2000	2000g x 1 g	2 lb
103103.....	C5000	5000g x 1 g	2lb

OPTIONS/ACCESSORIES

70434.....	80859975.....	Bowl for CS compact scales (1050ml)	
33423.....	90524-66	AC adapter for CL.....	
103521.....	80010624.....	Carrying case for CS and CL scales.....	
33455.....	5076-00	Aluminum scoop, 1.5in x 2in (3.8cm x 5.1 cm), weight 4g	
33456.....	5077-00	Gold scoop, 2.25in x 3in (5.7cm x 7.6cm), weight 10g	
33454.....	4590-30	Black scoop, aluminum 4in x 3.5in (10.2cm x 8.9cm), weight 24g	

C&M SCALE
 CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
 Phone # (708) 771-0100
 Fax # (708) 771-0195