

STANDARD FEATURES



SP202/SP402

- Large stainless steel weighing surface
- Large 0.6in (15.24mm) high contrast Liquid Crystal Display (LCD)
- Integral security bracket
- Below balance weighing (includes hook)
- Sealed front panel and molded spill ring
- Stability indicator
- Overload and underload indicators
- Auto shut-off (user enabled/disabled)
- Low battery indicator
- Battery or AC operation (AC adapter included)
- Span calibration mass (included on SP202, SP402, SP401, SP601 models)
- Integral shipping lock
- Parameter lock switch

APPROVALS



SPECIFICATIONS

OVERALL DIMENSIONS:

7.56in W x 2.13in H x 8.27in D
(192mm W x 54mm H x 210mm D)

APPLICATION MODES:

Parts counting with average piece weight recalculation, percentage weighing, totalization, display hold

TARE RANGE:

Full capacity by subtraction

OPERATING TEMPERATURE:

50°F to 104°F (10°C to 40°C)

POWER REQUIREMENTS:

AC adapter (included) or four AA batteries (not included)

REPEATABILITY (STD. DEV):

SP202, SP402: 0.01 g
SP401, SP601, SP-602, SP2001, SP4001: 0.1 g
SP6000, SP6001: 1 g

LINEARITY:

SP202, SP402, SP602: ±0.01 g
SP401, SP601, SP2001, SP4001: 0.1 g
SP6000, SP6001: ±1 g

SHIPPING WEIGHT:

4 lb (1.8kg)

CALIBRATION:

Digital calibration from keypad

STABILIZATION TIME:

Three seconds

OVER RANGE CAPACITY:

Capacity ±90 d

PAN SIZE:

SP202, SP401, SP402, SP602: 4.7in (119mm) diameter
SP601, SP2001, SP4001, SP6000, SP6001: 6.5in x 5.5in (152.4mm x 175.2mm)

WARRANTY:

Two-year limited warranty

Weighing Modes									
Model	SP202	SP402	SP401	SP601	SP602	SP2001	SP4001	SP6000	SP6001
Capacity	200 g	400 g	400 g	600 g	600 g	2000 g	4000 g	6000 g	6000 g
Readability	0.01 g	0.01 g	0.1 g	0.1 g	0.01 g	0.1 g	0.1 g	1 g	0.1 g
g	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
kg	-	-	-	-	-	Yes	Yes	Yes	Yes
oz	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
lb	-	-	-	Yes	Yes	Yes	Yes	Yes	Yes
lb:oz	-	-	-	Yes	Yes	Yes	Yes	Yes	Yes
ozt	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
dwt	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

PART #	OHAUS MODEL #	DESCRIPTION	EST. SHIP WEIGHT
77654.....	SP202	200g x 0.01 g	4lb
77655.....	SP402	400g x 0.01 g	4lb
103099.....	SP602	600g x 0.01 g	4lb
77656.....	SP401	400g x 0.1 g	4lb
77657.....	SP601	600g x 0.1 g	4lb
77658.....	SP2001	2,000 g x 0.1 g	4lb
77660.....	SP4001	4,000 g x 0.1 g	4lb
103100.....	SP6001	6,000 g x 0.1 g	4lb
77661.....	SP6000	6,000 g x 1.0g	4lb

OPTIONS/ACCESSORIES

70422.....	77256-01	Hard shell carrying case.....	
77710.....	71147376	RS-232 interface with integrated cable.....	
77711.....	71147377	USB interface with integrated cable	
83222.....	12102320.....	115VAC adapter.....	
35263.....	76288-01	Security device.....	
67413.....	SW12W	WinWedge® TAL Software.....	
104767.....		Impact printer	
104770.....		Paper for PN 104767	
104771.....		Ribbon for PN 104767	

WinWedge is a registered trademark of TAL Software.

C&M SCALE
 CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
 Phone # (708) 771-0100
 Fax # (708) 771-0195