

GP100 / GP250

Electronic General Purpose Bench Scale



Replaces the traditional mechanical scales

- **Battery Operated**– Uses one 9 volt battery
- **Weight Hold Key**– Locks the weight reading when a large package blocks the display
- **Portable**– Attached handle allows for easy transport
- **Discrete Switch Keyboard Technology**– Unique key button design to ensure reliability and longevity
- **Internal Backlit Display**– Display is integrated into the scale base. 1" high back lit digits allow for easy visibility.
- **Electro-Mechanical Design**– Ensures greater accuracy even at higher weight capacities

GP100 / GP250 Electronic General Purpose Bench Scale

Features

Construction– 22 gauge steel with ribbed base designed to protect against damage to the scale

Display– Four large 1" H digits, back light LCD display

Keyboard Functions–

- Hold** Freezes weight on the display only when a weight of 3 lbs or more is placed on the scale
- TARE** Removes weight of empty container or item placed on the scale to obtain a net weight
- UNITS** Scrolls between pounds and kilograms
Turns scale on or off and returns scale to zero weight

Indicator Displayed Messages–

- L0** Battery is weak
After 5 minutes scale will turn off

Auto Zero tracking– Includes AZT (Auto Zero Tracking) at .5 or manual push button to reestablish zero reference when displayed weight is less than 2% of capacity

Overload Capacity– Capable of withstanding 400 lb or 200 kg of weight without damaging the scale

Auto Shutdown– To conserve battery life the display will shutdown after 2 minutes of non-use. Can be configured via the keypad for Off, 2 or 4 minutes.

Specifications

<u>Capacity (lb)</u>	<u>Capacity (kg)</u>
100 x 0.2 lb	45 x 0.1 kg
250 x 0.5 lb	110 x 0.2 kg

Accuracy– ± 3 displayed divisions

Dimensions–

Scale: 10.95" (L) x 12.50" (W) x 2.20" (H)
278 mm (L) x 318 mm (W) x 56 mm (H)

Shipping Carton: 13.35" L x 13.5" W x 3" H
339 mm (L) x 318 mm (W) x 76 mm (H)

Power– Internal Battery: One 9 volt (not included)
AC Adapter: 9 VDC @ 200 mA (included)

Operating Temp– 42° F to 104° F (5° C to 40° C)

Agency Approvals– UL/CUL power adapter; FCC

Scale Weight– 6 lb

Shipping Weight– 8 lb

C&M SCALE
Website: www.cmscale.com
Email: support@cmscale.com

Toll Free: (800) 243-3721
In Chicago: (708) 771-0195
Fax: (708) 771-0195