

LPS30 Bench Scale

Portable Bench Scale



Shown with optional foot switch

- **Accuracy**– 0.1% of full scale
- **Capacity**– 30 lb
- **Construction**– Low profile stainless steel platform with mild steel understructure, stainless steel/ABS indicator with wall bracket and desk mount included.
- **Platform Size**– 15" L x 12" W x 1" H
- **Display**– Five 0.625" digits LCD
- **Power**– Battery or AC power
- **Operator Keys**– On/Off/Zero, Tare, Units (lb/kg), Hold/Print
- **Optional Foot Switch**

LPS30 Portable Bench Scale

Features

Portion control and product quality requirements make this economic scale perfect for use in pizza parlors, sandwich and salad shops, bakeries and supermarkets. Great for use in food operations to build consistent products and help control ingredient costs. Optional remote switch allows zeroing of the scale without using your hands.

The dual power modes (battery and AC adapter) enable portability or permanent installation (both included).

A large, simple to read display can be wall or stand mounted for easy visibility and the push button switches work with gloved hands (wall and desk mount included).

The indicator cable is a coil style for durability and easy extension to the wall or desk mount display.

The LPS30 features a full-duplex RS-232 interface that can transmit and receive using a demand type protocol.

The durable low profile SST platform allows for easy weighing and cleanup. Although NOT suitable for washdown, this scale is perfect for an environment where wipe down sanitation is sufficient. The LPS30 is a low cost, versatile and portable scale.



Shown with optional foot switch

C&M SCALE
Website: www.cmscale.com
Email: support@cmscale.com

Specifications

Capacity– 30 lb x 0.01 lb/0.2 oz (15 kg x .005 kg)

Platform Size– 15" L x 12" W x 1" H
380 mm (L) x 305 mm (H) x 27 mm (W)

Indicator– 6.5" L x 3.2" H x 1.2" W
164 mm (L) x 81 mm (H) x 29 mm (W)

Display– Five 0.625" digits LCD



RS-232– 10' interface cable (DB-9) (included)

Keyboard– On/Off/Zero, Tare, Units (kg/lb), Hold/Print

Units– lb, kg, lb/oz

Power– Four (4) AAA batteries or 6 VDC, 500mA adapter, both included

Battery Life– 20 hours

Operating Temp– 41° F to 95° F (5° C to 35° C)

Packaging Dimensions–

Scale: 17" L x 15" W x 2.3" H
450 mm (L) x 400 mm (W) x 60 mm (H)

Shipping Weight– 11 lb (5 kg)

Option– Foot Switch

Certifications– Full FCC compliance, UL/CUL power adapter