



Weighing Technology



# Intell-Check™/ICT

SERIES

*A Higher Level of Precision...A Higher Level of Performance*







## Washdown Checkweighing Bench & Platform Scale



- Stainless Steel, Washdown
- Full Keyboard Tare
- Bi-directional RS 232 Interface
- Heavy Duty Construction
- Large Backlit HI-OK-LO Graphic Display
- Real Time Clock
- ICT Models  



Manufactured for Intelligent Weighing Technology by an ISO 9001 certified company.

Model	Intell-Check60	Intell-Check150	Intell-Check300	ICT-150  	ICT-300  	ICT-500  
Capacity	60 kg / 132 lb	150 kg / 330 lb	300 kg / 660 lb	150 lb / 75 kg	300 lb / 150 kg	500 lb / 250 kg
Readability	0.01 kg / 0.02 lb / 0.5 oz	0.02 kg / 0.05 lb / 1 oz	0.05 kg / 0.1 lb / 2 oz	0.05 lb / 0.05 kg	0.1 lb / 0.05 kg	
Divisions	6000	7500	6000	5000		
Weighing Units	kg, lb, oz			NTEP or MC: lb, kg only / Non-NTEP or Non-MC: Primary units - kg, lb, oz (Gn, dwt, ct, lb:oz, g also available)		
Functions	Checkweighing with memory store and recall, limit and target weight modes, net/gross function, pre-tare function, time/date, lot #, accumulation (only with printer), percentage, signals for relay output					
Tare Range	To capacity by subtraction					
Power Source	Built-in rechargeable battery or external power adapter (included) or 120 V (please specify)					
Construction	Stainless steel indicator and pillar – stainless steel platform with aluminum load cell and load receiving structure			Stainless steel indicator and pillar – all stainless steel platform with aluminum load cell		
Display	Large backlit graphic HI-OK-LO checkweighing LCD display					
Platform Size (W x D x H)	16.7 x 20.7 x 4.7 inches / 425 x 525 x 120 mm			18 x 18 x 6 inches / 457 x 457 x 152 mm		
Overall Dimensions (W x D x H)	16.7 x 20.7 x 37 inches / 425 x 525 x 935 mm			18 x 18 x 37 inches / 457 x 457 x 935 mm		
Interface (included)	RS 232 Bi-directional or serial printer output, real time clock for time and date printing					
Net Weight	48.4 lb / 22 kg					
Shipping Weight	50 lb / 22.3 kg					
Nema / IP Rating	Indicator - NEMA 4X / IP 67 Platform - IP 65			Indicator - NEMA 4X / IP 67 Platform - IP 66		
Approvals	N/A			Indicator – NTEP CoC # 07-110, Measurement Canada Approval #AM-5651 Platform – NTEP CoC # 04-099		
Options	4 inch Stainless steel wheel kit					
Accessories	Printers					

### Features

- Lightweight
- Large backlit display
- Auto zero tracking
- Low battery indicator
- Automatic power save
- Adjustable weighing speed filters
- HI-OK-LO graphic display with configurable buzzer output
- Gravitational correction software
- Accumulation function (only with printer)
- RS 232 Interface

### Benefits

- Easy to use
- Can be easily read in less than ideal conditions
- Ensures that you always start weighing at zero
- Alerts you to charge battery, saving downtime
- Conserves battery power
- Allows you to adjust for operational and environmental conditions
- Makes checkweighing fast and easy
- Enables you to input different G acceleration factors
- Allows you to add together consecutive weights to arrive at a total
- Allows connection to printers or computers



Weighing Technology

# C&M SCALE

Website: [www.cmscale.com](http://www.cmscale.com)

Email: [support@cmscale.com](mailto:support@cmscale.com)

Toll Free: (800) 243-3721  
In Chicago: (708) 771-0195  
Fax: (708) 771-0195