



Weighing Technology

A Higher Level of Precision...A Higher Level of Performance

Intell-Weigh™

SERIES

Washdown Bench & Platform Scale

- NTEP Approved
- Stainless Steel, Washdown – Nema 4X / IP 67 Protection
- Bi-directional RS 232 Interface
- Heavy Duty Construction
- Real Time Clock
- AC/DC Adapter and Rechargeable Battery or 120 VAC Power Supply Option
- Easy Set Up and Configuration

NTEP  

Non-NTEP   



Manufactured for Intelligent Weighing Technology by an ISO 9001 certified company.



Model	IWT-150	IWT-300	IWT-500
Capacity	150 lb / 75 kg	300 lb / 150 kg	500 lb / 250 kg
Readability	0.05 lb / 0.05 kg	0.1 lb / 0.05 kg	0.1 lb / 0.05 kg
Divisions	5000		
Weighing Units	NTEP: lb, kg only / Non-NTEP: Primary units - kg, lb, oz (Gn, dwt, ct, lb:oz, g also available)		
Functions	Net/gross, pre-tare function, checkweighing (parts counting, animal hold, peak hold non-NTEP)		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included) or 120 V (please specify)		
Construction	Stainless steel platform with aluminum load cell		
Display	1 inch high backlit LCD display		
Platform Size (W x D x H)	18 x 18 x 6 inches / 457 x 457 x 152 mm		
Overall Dimensions (W x D x H)	18 x 18 x 38 inches / 457 x 457 x 965 mm		
Interface (included)	RS 232 Bi-directional or serial printer output, real time clock for time and date printing		
Net Weight	48.4 lb / 22 kg		
Shipping Weight	52 lb / 23.3 kg		
Nema / IP Rating	Indicator - NEMA 4X / IP 67 / Platform - IP 66		
Approvals	Indicator - NTEP CoC # 07-110 / Platform - NTEP CoC # 04-099		
Options	4 inch Stainless steel wheel kit		
Accessories	Printers		

Features

- Large backlit display
- Auto zero tracking
- Built-in rechargeable battery or external power adapter
- Low battery indicator
- Automatic power save
- Adjustable weighing speed filters
- Gravitational correction software
- Hold function (non-NTEP model)

Benefits

- Can be easily read in less than ideal conditions
- Ensures that you always start weighing at zero
- Portability (Battery lasts approximately 120 hours)
- Alerts you to charge the battery, saving downtime
- Conserves battery power
- Allows you to adjust for operational and environmental conditions
- Enables you to input different G acceleration factors
- Both peak hold and hold functions are available to keep weight displayed while it is being recorded



Weighing Technology

C&M SCALE

Website: www.cmscale.com
Email: support@cmscale.com

Toll Free: (800) 243-3721
In Chicago: (708) 771-0195
Fax: (708) 771-0195