



STANDARD FEATURES

- Applications Programs: counting, weighing in percent, checkweighing, net-total formulation and mass unit conversion by toggling for accurate weighing within an application program.
- Built-in isoTEST function.
- LCD back list remote display continuously shows maximum weighing capacity and resolution
- Fast weighing results
- Bidirectional RS-232 standard interface
- ISO Cal
- GMP/GLP Printout
- Number/Alpha keys

SPECIFICATIONS

DIMENSIONS:

FB-BBE/CCE 9.5in W x 17.4in H x 11.6in D
 FBG-EDE 12.1in W x 21.2in H x 4.8in D

DISPLAY CABLE:

2.6ft

RATING:

Units <12 kg capacity rated IP54;
 units rated >16 kg rated IP65

BELOW BALANCE WEIGHT:

Includes a hook for all units <12kg; for all other units, use metric M8 screws, 8mm diameter, 80mm long

WARRANTY:

Two-year limited warranty
 One year accessories

RLWS PN	SARTORIUS PN	PLATFORM SIZE (IN)	# LOAD CELLS	CAPACITY		CAPACITY		EST. SHIP WEIGHT (LB)
				READABILITY (LB)		READABILITY (KG)	(G)	
102848	FB06BBE-S	5.1 dia	1	1.3	0.000002	0.62	0.001	24
102849	FB2CCE-S	8.5 X 8	1	4.8	0.00002	2.2	0.01	26
102850	FB6CCE-H	8.5 X 8	1	13.6	0.00002	6.2	0.01	26
102851	FB6CCE-S	8.5 X 8	1	13.6	0.002	6.2	0.1	26
102852	FB12CCE-S	8.5 X 8	1	26	0.002	12	0.1	26
102853	FB16EDE-H	15.8 X 11.8	1	35	0.002	16	0.1	50
102854	FBG34EDE-P	15.8 X 11.8	1	18/36/75	0.0002/0.0005/0.001	8/16/1934	0.1/0.2/0.5	50
102855	FBG34EDE-H	15.8 X 11.8	1	75	0.002	34	0.1	50
102856	FBG64EDE-S	15.8 X 11.8	1	141	0.002	64	1	50
102857	FBG64EDE-H	15.8 X 11.8	1	141	0.0002	64	0.1	50

OPTIONS/ACCESSORIES

36907	YDP03-OCE	Data printer, statistics & T/D function, 5 ft cable (requires 83248)
31106	6906918	Ribbon
31103	6906937	Paper
83248	YCC01-0016MS	Cable 9.8ft, 12 pin round to 25D-sub female
32636	YRBO6Z	Battery pack, external rechargeable, approx 28 hours
31080	6971899	220V power supply
31117	IDAC-97	Digital to analog converter (specify scale & output) 25-D sub, 5 ft-requires 83248 cable