



STANDARD FEATURES

- Dot matrix three color Liquid Crystal Display (LCD)
- Two modes of operation, standard and TEP
- Internal resolution of 1/1,000,000
- 200 item memory
- Setpoint capabilities: internal buzzer or external relay devices
- Four RS-232 ports: printer, scanner, setpoint or PC
- Built-in real time clock

SPECIFICATIONS

INTERNAL RESOLUTION:

1/1,000,000

DISPLAY RESOLUTION:

1/25,000, 1/50,000, 1/100,000

DISPLAY:

Dot Matrix, Liquid Crystal Display (LCD)
 Three color: Green, Yellow and Red
 Weight: six-digits
 Unit Weight: five-digits
 Quantity: seven-digits

POWER SOURCE:

115/240 VAC (50/60Hz), 7W

INPUT SENSITIVITY:

0.4-2.0mV/V

LOAD CELL EXCITATION:

12VDC

OPERATING TEMPERATURE:

-10°C to +40°C

OPERATING HUMIDITY:

15% to 85% RH

NUMBER OF CHANNELS:

Two scales (1- internal and optional 1-4 x 350Ω load cells each)

PRINTER COMPATIBILITY:

RL-22DT
 RL-42DT with custom set-up
 ESCPOS compatible

INTERFACES:

4-RS-232
 Ethernet pending

MEMORY SETPOINT:

200 Items PLU

PROGRAMMABLE PER ITEM:

12 digit numeric part number
 Unit Weight
 Tare Weight
 Setpoint

PRINTING ITEMS:

ID code, net weight, gross weight, unit weight, tare weight, quantity, barcode (code 39)

DIMENSIONS:

Overall: 5in H x 14in W x 14.8in D
 128mm H x 356mm W x 376mm D

ESTIMATED SHIPPING WEIGHT:

13lb, 6kg

WARRANTY:

One-year limited warranty

PART #	DESCRIPTION	RESOLUTION WEIGHING	PLATTER	EST. SHIP WEIGHT
94909.....	DC-530, 10lb	0.0001lb	13in x 9.5in	13lb
94910.....	DC-530, 20lb	0.0002lb	13in x 9.5in	13lb

OPTIONS/ACCESSORIES

94911.....	Remote scale option (requires 32375)			
32375.....	14 pin load cell connector			
35319.....	14-pin load cell connector with 20ft of load cell cable			
95145.....	Manual, DC-530			
S-XL – Single Platform				
73278.....	S-XL Platform, 50lb		11 in x 16in	20lb (9kg)
73274.....	S-XL Platform, 100lb		11 in x 16in	20lb (9kg)

SCANNER/ACCESSORIES

65619.....	QS6000 RS-232 scanner and cable			
------------	---------------------------------------	--	--	--

PRINTERS/ACCESSORIES

65617.....	Label 2.25 x 4.5in with perf DTL			
64661.....	Cable for RL-22DT,RL-42DT, RL-420TT; 8-pin to 9-pin			
23113.....	Epson, TM-U295			
81076.....	Epson, TM-U220			
32810.....	8 pin to 25 pin RS-232 cable			
107403.....	RL-22DT printer, 110/230VAC, RS-232			

For additional platforms, please refer to Bench or Floor Scales Section.

C&M SCALE
 CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
 Phone # (708) 771-0100
 Fax # (708) 771-0195