

NEW

Digi® DC-782 Series

Portable Counting Scales



STANDARD FEATURES

- Liquid Crystal Display (LCD) with yellow backlight
- RS-232 output to PC
- 10 preset keys for product ID
- 25 item memory
- Internal resolution of 1/500,000
- Buzzer - low, ok, high

* Batteries not included

SPECIFICATIONS

INTERNAL RESOLUTION:

1/500,000

WEIGHT DISPLAY RESOLUTION:

1/7500 (1/6000)

DISPLAY:

Liquid Crystal Display (LCD) with backlight
Weight: Five-digit
Unit Weight: Five-digits
Quantity: Six-digit

POWER SOURCE:

AC power supply or optional rechargeable battery

NUMBER OF SCALE CHANNEL:

One local scale

MEMORY ITEMS:

25

RS-232:

9 Pin to PC

OPTIONAL BATTERY:

Charge time: 12-14 hours
Battery life: 300 hours (no backlight)

OPERATING TEMPERATURE:

14°F to 104°F (-10°C to 40°C)

DIMENSIONS:

Overall: 335.7 W x 349.7 D x 123.5 mm H
(8526.8 W x 8882.4 L x 3136.9 inH)

ESTIMATED SHIPPING WEIGHT:

5 kg

PLATTER SIZE:

300 x 225 mm (12 x 8.9 in)

WARRANTY:

Two-year limited warranty

Digi® DC-688 Series

Portable Counting Scales



STANDARD FEATURES

- Extra-wide stainless steel platter
- Three large numeric Liquid Crystal Displays (LCD) for weight, unit weight and quantity
- Six preset unit weight recall memory keys
- Count accumulation and subtraction function
- Negative sampling and counting (count out of a full container)
- Numeric keyboard
- Push-button or keyboard tare entry
- Net/gross weight display switching
- Internal buzzer
- 115VAC power
- Battery* - saving auto power-off function (selectable settings: 3 minutes, 10 minutes, 30 minutes, 1 hour, 3 hours, disabled)

* Batteries not included

SPECIFICATIONS

INTERNAL RESOLUTION:

1/30,000

WEIGHT DISPLAY RESOLUTION:

1/6000 (1/7500)

DISPLAY:

Liquid Crystal Display (LCD)
Weight: Five-digit
Unit Weight: Five digits
Quantity: Six-digit

POWER:

115VAC
9V provided by six "D" cell batteries (500 continuous hours with standard "D" cell batteries, 1,000 hours with "D" cell alkaline batteries)
* Batteries not included

POWER CONSUMPTION:

1.5W

FREQUENCY:

50 or 60 Hz

OPERATING TEMPERATURE:

14°F to 104°F (-10°C to 40°C)

DIMENSIONS:

Overall: 14.44 in L x 13.5 in W x 4.68 in H
(367 mm L x 343 mm W x 119 mm H)
Platter: 13 in L x 10 in W
(330.2 mm L x 254 mm W)
Carrying case (inside):
15 in L x 17 in W x 7 in H
(381 mm L x 431.8 mm W x 177.8 mm H)

ESTIMATED SHIPPING WEIGHT:

15 lb (7 kg)

WARRANTY:

Two-year limited warranty

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195

DC-782 Series

PART #	DESCRIPTION	CAPACITY	EST. SHIP WEIGHT
108248.....	DC-782	6 lb x 0.001 lb	11 lb (5 kg).....
108249.....	DC-782	15 lb x 0.002 lb	11 lb (5 kg).....
108250.....	DC-782	30 lb x 0.005 lb	11 lb (5 kg).....
108251.....	DC-782	60 lb x 0.01 lb	11 lb (5 kg).....

Consult factory for kg unit models.

OPTIONS/ACCESSORIES

108516.....	Rechargeable battery.....		
108517.....	AC adapter 110VAC.....		
108518.....	AC adapter 230VAC.....		

DC-688 Series

PART #	DESCRIPTION	CAPACITY	EST. SHIP WEIGHT
74023.....	DC-688	6 lb x 0.001 lb	15 lb (7 kg).....
74024.....	DC-688	15 lb x 0.002 lb	15 lb (7 kg).....
74025.....	DC-688	30 lb x 0.005 lb	15 lb (7 kg).....
74026.....	DC-688.....	60 lb x 0.01 lb	15 lb (7 kg)

Consult factory for kg unit models.

OPTIONS/ACCESSORIES

73189.....	Six "D" cell alkaline batteries		
73296.....	Carrying case		
73353.....	Additional operating manual.....		

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195