

Intercomp CS™ 200



STANDARD FEATURES

- Lightweight and compact
- Digital calibration
- Auto shut-off
- lb/kg selectable
- Peak hold feature

APPROVALS



SPECIFICATIONS

RESOLUTION:

12 bit A/D delivers more than 1 million internal counts

CONTROLS:

Zero, lb/kg, on/off

DISPLAY:

0.5 in (12mm) 5-digit LCD

POWER:

One 9V disposable alkaline dry cell (or rechargeable nickel-cadmium cell, not included) Battery life is one year of normal use.

DIMENSIONS: (W x D x H)

3.75 in W x 2 in D x 6 in H
(94 mm W x 50 mm D x 150 mm H)

ENCLOSURE:

Weatherproof ABS plastic case

APPROVALS:

CE

AUTO SHUT-OFF:

Low battery, or after 5 minutes without use

ACCURACY:

±0.1% of applied load

TEMPERATURE:

Operating -4°F to 140°F
(-20°C to 60°C)

NOMINAL OVERLOAD:

200% of capacity



MAXIMUM OVERLOAD:

500% of capacity

WARRANTY:

One-year limited warranty

PART #	CAPACITY	GRADUATION	EST. SHIP WEIGHT
CS200			
43734.....	25 lb (12.5 kg).....	0.01 lb (0.01 kg).....	2 lb
43735.....	50 lb (25 kg).....	0.02 lb (0.01 kg).....	2 lb
43736.....	100 lb (50 kg).....	0.05 lb (0.02 kg).....	2 lb
43737.....	250 lb (125 kg).....	0.1 lb (0.05 kg).....	2 lb
82444.....	500 lb (250 kg).....	0.2 lb (0.1 kg).....	2 lb



C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195

PART #	DESCRIPTION	EST. SHIP WEIGHT
CS200 (battery included):		
43734.....	CS200, 25 lb (12.5 kg) x 0.01 lb (0.01 kg).....	2 lb.....
43735.....	CS200, 50 lb (25 kg) x 0.02 lb (0.01 kg).....	2 lb.....
43736.....	CS200, 100 lb (50 kg) x 0.05 lb (0.02 kg).....	2 lb.....
43737.....	CS200, 250 lb (125 kg) x 0.1 lb (0.05 kg).....	2 lb.....
82444.....	CS200, 500 lb (250 kg) x 0.2 lb (0.1 kg).....	2 lb.....