

RoughDeck® HP-H

Heavy Capacity Floor Scale



STANDARD FEATURES

- Heavy-duty industrial design
- Structural steel channel frame
- Four NTEP Certified alloy steel, shear beam load cells
- 20ft SURVIVOR® EL147HE hostile environment load cell cable
- TuffSeal® JB4SS stainless steel, NEMA 4X j-box with signal trim card
- Side-entry j-box
- Rugged diamond safety treadplate deck
- Four adjustable stainless steel SUREFOOT™ support feet
- Threaded eyebolt holes for easy lifting
- Five-year limited warranty

APPROVALS



Measurement
Canada
Approved



SPECIFICATIONS

APPROVALS:

NTEP - certified, CC# 92-001A9
Class III, 5000d
Measurement Canada approved, AM-5284

END LOAD CAPACITY:

100% full scale at 20,000lbs
66% full scale at 30,000lbs

CABLE LENGTH:

20ft (6.1 m) for connecting j-box to indicator

WARRANTY:

Five-year limited warranty

BASES

PART #	PART #	SIZE (W x L x H)	CAPACITY	EST. SHIP WEIGHT
w/Quick Connector	w/out Quick Connector			
66474	67717	4 ft x 4 ft x 4 in	20,000lb (10,000kg)	601 lb
66475	67718	4 ft x 5 ft x 4 in	20,000lb (10,000kg)	775 lb
66476	67719	4 ft x 6 ft x 4 in	20,000lb (10,000kg)	926 lb
66477	67720	4 ft x 7 ft x 4 in	20,000lb (10,000kg)	1,135 lb
66478	67721	5 ft x 5 ft x 4 in	20,000lb (10,000kg)	926 lb
66479	67722	5 ft x 6 ft x 4 in	20,000lb (10,000kg)	1,104 lb
66480	67723	5 ft x 7 ft x 4 in	20,000lb (10,000kg)	1,377 lb
66481	67724	6 ft x 6 ft x 4 in	20,000lb (10,000kg)	1,319 lb
66482	67725	6 ft x 8 ft x 4 in	20,000lb (10,000kg)	1,861 lb
66483	67726	7 ft x 9 ft x 4 in	20,000lb (10,000kg)	2,408 lb
66484	67727	7 ft x 10 ft x 4 in	20,000lb (10,000kg)	2,959 lb
66485	67728	8 ft x 10 ft x 4 in	20,000lb (10,000kg)	3,108 lb
66486	67729	4 ft x 4 ft x 5 in	30,000lb (15,000kg)	675 lb
66487	67730	4 ft x 5 ft x 5 in	30,000lb (15,000kg)	839 lb
66488	67731	4 ft x 6 ft x 5 in	30,000lb (15,000kg)	1,071 lb
66489	67732	4 ft x 7 ft x 5 in	30,000lb (15,000kg)	1,200 lb
66490	67733	5 ft x 5 ft x 5 in	30,000lb (15,000kg)	1,021 lb
66491	67734	5 ft x 7 ft x 5 in	30,000lb (15,000kg)	1,448 lb
66492	67735	6 ft x 6 ft x 5 in	30,000lb (15,000kg)	1,438 lb
66493	67736	7 ft x 10 ft x 5 in	30,000lb (15,000kg)	3,372 lb
66494	67737	8 ft x 10 ft x 5 in	30,000lb (15,000kg)	3,699 lb

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195

PART # w/Quick Connector	PART # w/out Quick Connector	SIZE (W X L X H)	CAPACITY	EST. SHIP WEIGHT
66474.....	67717.....	4 ft x 4 ft x 4 in	20,000 lb (10,000 kg).....	601 lb.....
66475.....	67718.....	4 ft x 5 ft x 4 in	20,000 lb (10,000 kg).....	775 lb.....
66476.....	67719.....	4 ft x 6 ft x 4 in	20,000 lb (10,000 kg).....	926 lb.....
66477.....	67720.....	4 ft x 7 ft x 4 in	20,000 lb (10,000 kg).....	1,135 lb.....
66478.....	67721.....	5 ft x 5 ft x 4 in	20,000 lb (10,000 kg).....	926 lb.....
66479.....	67722.....	5 ft x 6 ft x 4 in	20,000 lb (10,000 kg).....	1,104 lb.....
66480.....	67723.....	5 ft x 7 ft x 4 in	20,000 lb (10,000 kg).....	1,377 lb.....
66481.....	67724.....	6 ft x 6 ft x 4 in	20,000 lb (10,000 kg).....	1,319 lb.....
66482.....	67725.....	6 ft x 8 ft x 4 in	20,000 lb (10,000 kg).....	1,861 lb.....

BASES

PART #	PART #	SIZE (W x L x H)	CAPACITY	EST. SHIP WEIGHT
66483.....	67726.....	7 ft x 9 ft x 4 in	20,000 lb (10,000 kg).....	2,408 lb.....
66484.....	67727.....	7 ft x 10 ft x 4 in	20,000 lb (10,000 kg).....	2,959 lb.....
66485.....	67728.....	8 ft x 10 ft x 4 in	20,000 lb (10,000 kg).....	3,108 lb.....
66486.....	67729.....	4 ft x 4 ft x 5 in	30,000 lb (15,000 kg).....	675 lb.....
66487.....	67730.....	4 ft x 5 ft x 5 in	30,000 lb (15,000 kg).....	839 lb.....
66488.....	67731.....	4 ft x 6 ft x 5 in	30,000 lb (15,000 kg).....	1071 lb.....
66489.....	67732.....	4 ft x 7 ft x 5 in	30,000 lb (15,000 kg).....	1,200 lb.....
66490.....	67733.....	5 ft x 5 ft x 5 in	30,000 lb (15,000 kg).....	1,021 lb.....
66491.....	67734.....	5 ft x 7 ft x 5 in	30,000 lb (15,000 kg).....	1,448 lb.....
66492.....	67735.....	6 ft x 6 ft x 5 in	30,000 lb (15,000 kg).....	1,438 lb.....
66493.....	67736.....	7 ft x 10 ft x 5 in	30,000 lb (15,000 kg).....	3,372 lb.....
66494.....	67737.....	8 ft x 10 ft x 5 in	30,000 lb (15,000 kg).....	3,699 lb.....

OPTIONS/ACCESSORIES

N/A.....	Smooth deck instead of diamond safety tread plate.....
40387.....	Mounting plate, mild steel, 20K capacity models (optional).....
40388.....	Mounting plate, mild steel, 30K capacity models (optional).....
N/A.....	Four drilled deck holes for scale height adjustment
19352.....	RoughDeck floor stand for indicator, 36.3in high, mild steel.....
66662.....	Additional operating manual.....
MS-1*.....	Mild steel deck with RLWS stainless steel FM approved load cells and hardware.....
MS-2*.....	Mild steel deck with RLWS welded seal IP67 stainless steel FM approved load cells, and hardware.....
MS-10.....	Epoxy paint.....
MS-11.....	Top access j-box

* Load cell and junction box substitution

Access ramps, pit frames, bumper guards and portability frames available. See pages F-39 thru F-48

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195