

# Pegasus Floor Scale Systems

Calibrated Platform Scale with Indicator



*4'x4' Pegasus System shown  
with optional indicator stand*

- **Pre-calibrated**– Indicator and floor scale calibrated at the factory prior to shipment
- **Capacity, Size**– Match a capacity and size with one of five Salter Brecknell indicators
- **Easy Installation**– Units can be placed into service with no on-site installation required
- **A/D Conversion Rate**– Up to 25 measurements per second

VALUE IN  
WEIGHING

# Pegasus Floor Scale Systems

## Capacities & Resolution

Capacity	Dimension-in.	Dimension-cm
5,000 x 1 lb (2500 x .5 kg)	48 x 48 x 3.1 60 x 60 x 3.1	122 x 122 x 7.9 152 x 152 x 7.9
10,000 x 2 lb (5000 x 1 kg)	48 x 48 x 3.1 60 x 60 x 3.1	122 x 122 x 7.9 152 x 152 x 7.9

All capacities and resolutions shown above are based on 5000d.

## Indicator Interface Cable

**Models 200E**– 14 pin Centronics connector, 15 ft

**Model SBI 140**– Includes quick disconnect, 15 ft



## Model SBI 140 Indicator

For non legal for trade applications

**Easy to Read**– LCD display

**Construction**– Stainless steel/ABS enclosure

**Power**– 115 VAC, internal batteries

**Excitation Voltage**– 4.4 VDC

**Serial Port**– One full duplex RS-232

**Digital Calibration**– Front panel

**Keyboard**– On/Off/Zero, Tare, Units, Hold

**Units**– Kg, Lb, Lb:Oz

## Material Specifications

**Platform**– Mild steel

**J-Box**– ABS Plastic

**Finish**– Powder coat paint

**Approvals**– NTEP and Non NTEP systems

## Loadcell Specifications

**Material**– Alloy tool steel potted

**Rated Output**– 3 mv/V

**Output Resistance**– 350 ohm



## Model 200E / 200ES Indicator

**Easy to Read**– 0.6" (15 mm) LED display

**Construction**–

200E: ABS NEMA 12 enclosure

200ES: NEMA 4X stainless steel enclosure

**Power**–

200E: 115 VAC  $\pm 10\%$

200ES: 115/230 VAC  $\pm 10\%$

**Excitation Voltage**–  $\pm 5$  VDC, 4 x 350 ohm loadcells

**Serial Port**– One full duplex RS-232

**Digital Calibration**– Front panel calibration and configuration

**Keyboard**– Units, Zero, Net/Gross, Tare, Print

**Functions**– Gross/Net/Tare; Print ticket mode; Simple piece counting

**Units**– Switch between lb and kg

**Stand**– Stainless steel swivel stand included

**Display**– Up to 50,000 graduations

**Certifications**– NTEP at 5,000d, Class III,

COC #00-065

**C&M SCALE**  
Website: [www.cmscale.com](http://www.cmscale.com)  
Email: [support@cmscale.com](mailto:support@cmscale.com)

Toll Free: (800) 243-3721  
In Chicago: (708) 771-0195  
Fax: (708) 771-0195