


Pegasus Floor Scales

Platform Scale



NTEP CC 02-070



- **Rugged Construction**– Up to 0.25" (6 mm) thick top plate with heavy duty welded channel support
- **Legal for Trade**– All sizes are NTEP certified at 5,000 divisions
- **Low Profile**– 3.1 inches high using 1.75" adjustable leveling feet
- **Finish**– Powder coat paint
- **Versatile**– Pit mounted or free standing
- **Loadcells**– Four alloy tool steel potted loadcells
- **Available in mild steel or all stainless steel construction**

VALUE IN
WEIGHING

Pegasus Floor Scales Platform Scale

J-Box Access– Top access for easy installation and service

Leveling Feet– Four top access holes for a quick installation

Threaded Eye Bolts– Two threaded top access eye-bolt holes for easy mobility and pit service

Corner Protection– Closed corners to prevent damage to leveling feet while installing the scale

Capacities & Resolution

Capacity	Model	Dimension-in.	Dimension-cm
2,000 x 5 lb (1000 x .2 kg)	DCSB3636-02	36 x 36 x 3.1	91 x 91 x 7.9
5,000 x 1 lb (2500 x .5 kg)	DCSB3636-05	36 x 36 x 3.1	91 x 91 x 7.9
	DCSB4848-05	48 x 48 x 3.1	122 x 122 x 7.9
	DCSB6048-05	60 x 48 x 3.1	152 x 122 x 7.9
	DCSB7248-05	72 x 48 x 3.1	183 x 122 x 7.9
	DCSB6060-05	60 x 60 x 3.1	152 x 152 x 7.9
10,000 x 2 lb (5000 x 1 kg)	DCSB4848-10	48 x 48 x 3.1	122 x 122 x 7.9
	DCSB6048-10	60 x 48 x 3.1	152 x 122 x 7.9
	DCSB7248-10	72 x 48 x 3.1	183 x 122 x 7.9
	DCSB6060-10	60 x 60 x 3.1	152 x 152 x 7.9

All capacities and resolutions shown above are based on 5000d

Rugged Construction



Wide channel design for superior durability

General Floor Scale Specifications

Platform Material

Construction: Mild steel
.25 inch deck with safety tread,
10K (4' x 6'; 4' x 5'; 5' x 5')
.19 inch deck with safety tread,
2 - 10K (3' x 3'; 4' x 4')

Finish– Powder coat paint

J-Box Construction– ABS plastic

Loadcell Material– Alloy tool steel potted

Loadcell Rated Output– 3 mv/V

Loadcell Output Resistance– 350 ohm

Overload Protection– 150% of rated capacity

End Loading– 100% of rated capacity

Temperature– 14° F to 104° F (-10° C to 40° C)

Accuracy– NTEP at 5000 divisions, Class III

Certifications– NTEP COC #02-070

Options

Ramps– Up to four ramps can be used with the Pegasus family

Indicators– The Pegasus can be used with a variety of electronic indicators

Pit Frames– Mild steel frames

Indicator Stand– 48" high, mild steel, powder coat painted, for the Salter Brecknell 200E or 200ES indicator. Includes stand, mounting hardware and floor mount baseplate.

C&M SCALE
Website: www.cmscale.com
Email: support@cmscale.com

Toll Free: (800) 243-3721
In Chicago: (708) 771-0195
Fax: (708) 771-0195