



STANDARD FEATURES

- Display shows any combination of wheel weights or percentages of weight: left side, wedge, etc.
- Easy-to-use automatic zero and keypad calibration
- High accuracy and repeatability
- Full one-year warranty
- Units of measure: lb/kg
- Lightweight, low-profile weigh pads, 15 in L x 15 in W x 4 in H
- Weigh pads have leveling feet and handles
- Large Liquid Crystal Display (LCD)
- Powered by six AA batteries

SPECIFICATIONS

GENERAL CONTROLS:

Zero, on, off, weight/%

CHANNEL SELECTION:

Left front (LF), right front (RF), left rear (LR), right rear (RR), All

WEIGHT & PERCENT:

Weight and percent selection indicators: Lo bat, lb/kg

SPEED:

950 milliseconds to typical reading (static)

ACCURACY:

± 0.1% or 1 lb/0.5kg

CALIBRATION:

Keypad calibration

UNITS OF MEASURE:

lb, kg selectable

VOLTAGE:

12/VDC, 115/230 VAC

BATTERIES:

AA size rechargeable Ni-cad or alkaline

HUMIDITY:

10 to 95% non-condensing

TEMPERATURE:

Operating: 32°F to 122°F (0°C to 50°C)
Storage: -40°F to 170°F (-40°C to 75°C)

WEIGH PAD (W X L X H):

Overall dimensions: 15 in x 15 in x 4 in
Weight: 23 lb (10.5 kg)
Material: Aerospace grade cast aluminum

WARRANTY:

One-year limited warranty

DIMENSIONS					
PART #	MODEL	WEIGH PAD SIZE	CAPACITY	GRADUATION	EST. SHIP WEIGHT
43688	SWII 4000	15 in X 15 in X 4 in	4,000 lb (1800 kg)/1,000 lb (450 kg) per pad	1 lb (0.5 kg)	105 lb (47.6 kg)
43689	SWII 6000	15 in X 15 in X 4 in	6,000 lb (2800 kg)/1,500 lb (700 kg) per pad	1 lb (0.5 kg)	105 lb (47.6 kg)

PART #	MODEL	PAD SIZE	WEIGH CAPACITY	EST. SHIP WEIGHT
43688.....	SWII-4000	15 in x 15 in	4,000 lb	105 lb
43689.....	SWII-6000	15 in x 15 in	6,000 lb	105 lb

OPTIONS/ACCESSORIES

43948..... Serial RS-232 output

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195