

Dymo® SE300 Printer



STANDARD FEATURES

- Easy-to-read full label format with date and time
- Fast and accurate printing of ID, UW, QTY, tare and bar codes
- Silent print and quiet operation
- Maximum print speed 2 inches/second
- 23 internal bar code symbologies
- Power cord and 9DB9 female serial cable included
- Compatible with DIGI® scales: DC-190, DMC-290, DC-200/300 with 73106
- Maximum print width: 2.20in
- ASCII printer

APPROVALS



SPECIFICATIONS

PRINT METHOD:

Direct thermal

PRINT HEAD DENSITY:

203 dpi

PRINT HEAD LIFE EXPECTANCY:

2,000,000 linear inches

MAXIMUM PRINT SPEED:

2 inches/second

INTERFACE:

RS-232 serial selectable 1200-115,200 baud, no parity, 8 data bits, 1 stop bit

MEMORY:

30K RAM for graphics buffer, 4K data input buffer

MAXIMUM MEDIA THICKNESS:

0.006in (0.152mm) card stock

POWER REQUIRED:

115V

DIMENSIONS:

5 in W x 5.25 in H x 7.25 in D
(124 mm W x 133 mm H x 184 mm D)

APPROVALS:

UL listed

ESTIMATED SHIPPING WEIGHT:

1.25lb (0.57 kg)

WARRANTY:

One-year limited warranty

PART#	DESCRIPTION	EST. SHIP WEIGHT
73093.....	SE300 printer 9-pin DBF.....	1.25lb

OPTIONS/ACCESSORIES

74657.....	Label, 2.125 in x 2.75 in, 320 labels/roll, 3 rolls/case	
73114.....	Label, 2.3 in x 4.5 in, 250 labels/roll, 3 rolls/case	
73115.....	Label, 2.125 in x 2.75 in, 320 labels/roll	
74552.....	Label, 2.312 in x 4.5 in.....	
73118.....	Label 2.3 in x 4.0 in, 300/roll.....	
73117.....	Paper, thermal	
81211.....	Adjustable spool	
81210.....	Power Cord	

CABLES

73106.....	Cable, RJ-11 to male 8-pin DIN (required for DC-190/DC-200/300).....
81209.....	Cable, RS-232 DB9F

C&M SCALE
 Website: www.cmscale.com
 Email: support@cmscale.com

Toll Free: (800) 243-3721
 In Chicago: (708) 771-0195
 Fax: (708) 771-0195