



STANDARD FEATURES

- Epson M190 Series impact printhead
- Low power printer driver
- Fail safe circuits
- Paper-out sensor
- Power on/off circuit
- Auto shut-off
- Membrane switch for user input
- Battery operation
- Includes battery, AC adapter, auto ranger charger and one roll of paper
- RS-232 and Infrared (IrDa) communication interface
- Epson compatible printer driver
- Enclosed paper supply
- Operates from either standard 5-cell metal hydride battery cartridge or AC power adapter
- Tear bar

SPECIFICATIONS

PRINT SPEED:

60cps

PRINT METHOD:

Impact dot matrix

DOT/LINE:

144 (24 column)

CHARACTER SIZE:

2.6mm x 1.1 mm (40 column)

CHARACTER SIZE:

2.6mm x 1.1 mm

RIBBON TYPE:

2.6mm x 1.1mm (40 column) (printhead line 900,000 lines)

NUMBER OF COLUMNS:

24

PAPER LOADING:

Auto paper loading

PAPER WIDTH:

2.25in (57 mm)

LINE BUFFERING:

32K standard with IrDA

INTERFACE:

RS-232 Infrared (IrDA)

BAND RATE:

2400, 4800, 9600, 19,200

POWER:

5 cell NiMH (rechargeable) battery AC/DC adapter, 100-240VAC

POWER CHARGING:

Quick charge circuitry, recharges in 90 minutes

BATTERY OPERATION:

Prints up to 22,500 lines per charge

CONNECTION:

RJ25, 6-pin

WEIGHT:

1.5lb

OPERATING TEMPERATURE:

-10°C to 50°C

STORAGE TEMPERATURE:

-20°C to 60°C

OVERALL DIMENSIONS:

4.25in x 5in x 2 7/8in

WARRANTY:

One-year limited warranty

PART # DESCRIPTION

87384.....	2000i Portable Printer, RS-232 with power supply, 115-240VAC
88256.....	Tape printer 2000i DL with battery back time clock

OPTIONS/ACCESSORIES

87385.....	Spare battery (NiMH; 1600mAh)
87386.....	24 volt in-vehicle charger (must use battery in printer)
87389.....	Paper, 5 rolls (1/4 in core) Dia 1 7/16 Width 2 3/16.....
87387.....	Ink ribbon, purple.....
87388.....	RJ-25 to blunt end coiled cable
NA.....	Belt holder
NA.....	Thermal paper
88258.....	Cable RJ25-DB9
88261.....	2 ply paper roll (5 rolls)