



STANDARD FEATURES

- Double-strike high speed, 180 characters per second (cps)
- Single copy or up to five-part multicopy forms
- Functions in slave capacity, printing information sent via RS-232 or weight extraction smart mode, processing information before printing
- Cash drawer kick-out function
- Inexpensive ink cartridge for no-mess ribbon changes
- Battery backup; optional time/date and consecutive number (or ID) are retained for a year or more in the event of a power failure
- Compatible with most Mettler-Toledo indicators

APPROVALS



SPECIFICATIONS

PRINT SPEED:

3.5 lines per second,
180 characters per second

CHARACTERS PER LINE:

40 characters at 12 cpi
Print Area: 3.33in (84.6mm) wide

CHARACTER FORMATION:

5 x 9 dot matrix

CHARACTER HEIGHT:

0.1 in (2.5mm) enhanced double-wide
or 0.45in (11.4mm) on 4X. Can be inverted
for left side of tickets

CHARACTER SET:

Full 96-character ASCII
(upper and lower case set)
Dimensions:
7 in H x 8 in W x 11 in L

LINE SPACING:

Six lines per inch (25.4 mm)

COPY CAPABILITIES:

Single copy or up to five-part
multicopy forms

PRINT MEDIA:

Form thickness adjustable
from 0.004 in to 0.026 in (0.1 to 0.7 mm)
by 0.004 in step increments

RIBBON:

Cartridge-type black or blue ink ribbon.
Ribbon life is approximately
1 million standard characters

SERIAL INTERFACES:

RS-232 standard, 20mA current loop
(passive only) or Centronics® Parallel

WEIGHT:

12 lb

BAUD RATES:

300, 600, 1200, 2400, 4800, 9600
or 19,200 selectable

PARITY:

1 parity bit (even ignored by printer)

APPROVALS:

UL & C-UL listed, CE marked

WARRANTY:

One-year limited warranty
(includes printhead)

EST. SHIP WEIGHT

PART # DESCRIPTION

34229.....	SP2200 Ticket Printer, 115VAC w/RS-232 (black/light gray).....	12 lb
35855.....	SP2200 Ticket Printer, 230VAC w/RS-232 (black/light gray).....	12 lb

SP2200 WITH TIME/DATE AND SWITCH MODULE

34228	SP2200 Ticket Printer, 115VAC w/RS-232 (black/light gray).....	12 lb
35856	SP2200 Ticket Printer, 230VAC w/RS-232 (black/light gray).....	12 lb

OPTIONS/ACCESSORIES

35231	Switch module.....
20232.....	Time/date clock chip
20302.....	20mA current loop.....
20308	Ink cartridge (black).....
21210	Protective dust cover
34282	Maintenance and service manual
34171	Additional operating manual.....

CABLES

15548	25-pin D-sub male to 25-pin D-sub male 20mA serial interface cable.....
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable.....

Interfaces to: Rice Lake indicators with a serial port screw terminal connection

Consult Custom 20mA/RS-232 serial interface cable